



Luminaire Efficiency: 73.6%

Life/ Maintenance

• LED Driver Average Rated Life	100 000hrs
• LED Life	72 000hrs (L80 F10, TP 65°C)

Application

- Offices
- Retail Stores
- Lecture Halls
- Reception Areas

Benefits

- **5 Year warranty**
- Built-in surge Protection

Product Features and Accessories

- High colour rendering index CRI > 80
- Colour temperature 4000K (3000K and 5000K on request)
- Small colour tolerance - MacAdam 3
- Tridonic LED module and driver
- Ambient temperature: -25...+45°C
- Surface or suspended luminaire
- Extruded aluminium body with frosted acrylic diffuser
- Available in matt black or white aluminium
- DALI/DSI and dimmable options available
- Emergency options available
- Custom lengths to order
- Available in standard 600mm, 1200mm, 1800mm, 2400mm
- Multiple wattage and lumen packages available

Specification	Lumen @ 65°C	System Power	Power Factor	Current	Dimensions				Weight
					L	L2	W	H	
H-PRO-S-12W-LED-600	2574	14.4W	0.98	275mA	580mm	530mm	62mm	66mm	0.65kg
H-PRO-S-24W-LED-1200	4561	26.7W	0.98	275mA	1140mm	1090mm	62mm	66mm	1.3kg
H-PRO-S-36W-LED-1800	6841	40.2W	0.98	275mA	1770mm	1720mm	62mm	66mm	1.95kg
H-PRO-S-48W-LED-2400	9122	53.4W	0.98	275mA	2400mm	2350mm	62mm	66mm	2.6kg

