



Luminaire Efficiency: 92.3%

Life/ Maintenance

• LED Driver Average Rated Life	100 000hrs
• LED Life	72 000hrs (L80 F10, TP 65°C)

Application

- Supermarkets
- Aisle Lighting
- Sport Halls
- Warehouses

Benefits

- **5 Year warranty**
- Built-in surge Protection

Product Features and Accessories

- High colour rendering index CRI > 80
- Colour temperature 4000K (3000K and 5000K on request)
- Small colour tolerance - MacAdam 3
- Tridonic LED module and driver
- Ripple current < 3%
- All fixtures component parts are replaceable
- Ambient temperature: -25...+45°C
- Single mount or continuous row lighting
- Supplied with fish plates for continuous row lighting
- End-caps ordered separately
- Suitable for mounting on trunking
- Suspension cables supplied separately
- DALI/DSI and dimmable options available
- Emergency options available
- High efficiency and high output versions

Specification	Lumen @ 65°C	System Power	Power Factor	Current	Dimensions			Weight
					L	W	H	
RAIL-N-55W-LED	10263	61.5W	0.98	275mA	1680mm	60mm	48mm	2.3kg
RAIL-N-80W-LED	14757	89.2W	0.98	400mA	1680mm	60mm	48mm	2.3kg

