



Luminaire Efficiency: 94.3%

Life/ Maintenance

- | | |
|---------------------------------|------------------------------|
| • LED Driver Average Rated Life | 50 000hrs |
| • LED Life | 50 000hrs (L80 F10, TP 45°C) |

Application

- Residential Lighting
- Shopping Malls
- Passage and walkways

Benefits

- **5 Year warranty**
- Built-in surge protection

Product Features and Accessories

- High colour rendering index CRI > 80 (CRI > 90 available on request)
- Colour temperature 4000K (3000K on request)
- Direct replacement for HID Metal Halide 20W to 35W
- Small colour tolerance – MacAdam 3
- Chemically treated and epoxy powder coated
- Available in a wide and narrow beam (34° and 19°)

Specification	Lumen @ 45°C	System Power	Power Factor	Current	Dimensions		Weight
					H	D	
SDL-150-12W-LED	2110	12.8W	0.98	350mA	150mm	100mm	1kg
SDL-150-17W-LED	2940	18.4W	0.98	500mA	150mm	100mm	1kg
SDL-200-17W-LED	2940	18.4W	0.98	500mA	200mm	100mm	1.2kg
SDL-200-25W-LED	4980	29.4W	0.98	800mA	200mm	100mm	1.2kg

