



Luminaire Efficiency: 84.7%

Life/ Maintenance

• LED Driver Average Rated Life	50 000hrs
• LED Life	55 000hrs (L80 F10, TP 45°C)

Application

- Offices
- Shopping Malls
- Double Volume Areas
- Lecture Halls
- Convention Halls

Benefits

- **5 Year warranty**
- Built-in surge Protection

Product Features and Accessories

- High colour rendering index CRI > 80 (CRI>90 available on request)
- Colour temperature 4000K and 3000K available
- Tridonic COB and driver
- Ripple current < 3%
- All fixtures component parts are replaceable
- Direct replacements for HID Metal Halide 20W to 50W
- Direct replacements for CFL 2x18W to 2x26W
- Fits into existing cut out of 165mm to 230mm
- Available in 50° beam angle
- Non-corrosive bezel
- Fully dimmable version on request

Specification	Lumen @ 45°C	System Power	Power Factor	Current	Dimensions			Weight
					Cut Out	D	H	
FUT6-12W-LED-840	2110	12.8W	0.98	350mA	165-230mm	300mm	208mm	1.2kg
FUT6-17W-LED-840	2940	18.4W	0.98	500mA	165-230mm	300mm	208mm	1.2kg
FUT6-20W-LED-840	3790	22.2W	0.98	600mA	165-230mm	300mm	208mm	1.2kg
FUT6-27W-LED-840	4980	29.4W	0.98	800mA	165-230mm	300mm	208mm	1.2kg

